

GoProtect

Paint Spot Remover

A Highly Effective & Versatile Remover of Multi-Layers of
Paints, Varnishes, Wood Stains & Lacquers



Painted wood surface

Paint Remover applied

Wiped off and paint removed

PRODUCT DESCRIPTION

Water based low odour, easy to use white gel with a pleasant almond odour.

Major features include:

- Slow drying
- Non-flammable;
- Non-Ozone depleting;
- Non-corrosive;
- Cost effective;
- Low V.O.C.;
- Excellent methylene chloride replacement

PACKAGING

250ml Bottle with Applicator

1 litre Bottle

ADVANTAGES & CHARACTERISTICS

Removes

- Paint
- Varnish
- Graffiti
- Artex
- Stains
- Lacquer

Suitable for:

- Wood
- Metal
- Brick

GoProtect Limited, 71-75 Shelton Street, London WC2 9JQ
Tel: 020 3911 5526. E-mail: info@goprotect.co

- Stone

APPLICATION INSTRUCTIONS

'Always test apply on a small hidden portion of the substrate'

- Cover top with a cloth during opening to avoid splashes.
- Always test a small area before use.
- Multi layers benefit from a second coat
- If leaving overnight cover with plastic to help the removal process.
- Apply a generous, even coat- do not brush out. Layer **PAINT REMOVER** onto surface to be stripped with a suitable clean brush.
- Leave for approximately 1- 2 hours and apply a second generous coat. On less than five layers of paint or varnish, a second coat may not be necessary.
- Once **PAINT SPOT REMOVER** has penetrated through to the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible.
- Rinse clean with cold water and a stainless steel scourers and leave to dry.
- In certain circumstances, it may be easier to remove first coating of **PAINT SPOT REMOVER** with scrappers and reapply if the surface coating is delaminating.
- It may be possible to enhance the performance of **PAINT SPOT REMOVER** by leaving the product for longer periods or in some circumstances overnight on extremely difficult coatings, ensuring the product is well coated and covered with plastic to avoid drying out.
- Check on the composition of coatings being removed, to ensure any historic lead-based coatings are present in which case disposal must be treated as toxic waste.
- All application and removal procedures to be in accordance with BS 6150:2006+A1:2014.
- How long does it take:
 - Paint: 5–30 mins.
 - Varnish: 5–30 mins.
 - 2-pack varnish: 30–60 mins.
 - 2-pack lacquer: 30 mins–4hrs.
 - Graffiti: 5 mins – 4 hrs.
 - Heavy multi-layered paint: 90 mins–overnight.

RECOMMENDATIONS

- Ensure surfaces to be stripped: (i) are dry, and (ii) adjacent floors & delicate surfaces are always protected.
- Always apply a thick generous coat.
- Do not spread the product too far because this may result in poor penetration
- Always let **PAINT REMOVER** do the work. The longer you leave it the more it will strip.
- Never allow the product dry out.

EQUIPMENT CLEANING

Immediately after you have finished, clean all tools and equipment with water.

STORAGE & SHELF LIFE

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

Do not use below 4°C. Avoid use in rainy conditions.

HEALTH & SAFETY

See Material Safety Data Sheet before use.

Important: The content of this documentation is based on our experience of the product. Lubelska Ltd. guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with GoProtect's products or bad weather conditions. For further information, refer to the safety data sheet.

LUBELSKA PRODUCT CODE: R-10