

# GoProtect SIMPLE SOLUTIONS

## Polished Granite Sealer

A High Performance Water and Stain Repellency Protection



Before

Panels spotted with water after 2 hours



After

### PRODUCT DESCRIPTION

Protects against:

- Water and moisture penetration
- Food and drink staining
- Mild Acids and Alkali cleaners
- Pollution & dirt contamination
- Bird fouling
- Vegetation, Algae, Lichen & Moss growth
- A treated surface will remain moisture vapour permeable.

### USES

A water based dispersion which protects polished granite and quartz, including kitchen work-tops, headstones, monuments.

### PACKAGING

500ml Sprayers

### PHYSICAL PROPERTIES

Invisible once dry

Vapour permeable (Sd value: 0.03)

Non-hazardous water borne product

Solvent and silicone-free

Fully biodegradable

UV-resistant

Colour: Colourless

Odour: Slight, soapy

Density: 1.0kgs/Ltr @ 25°C.

Consistency: Low viscosity liquid

Chemical resistance: Dilute acids & alkalis,  
de-icing salts, water

Combustibility: Non-combustible

## **APPLICATION INSTRUCTIONS**

***'Always test apply on a small hidden portion of the substrate'***

Substrate Quality: Cracks must be repaired using a repair system.

Moisture content should be = or <5% to a depth of 1cm.

substrate Preparation: Clean, free from dust, dirt, oil, efflorescence, organic growth and old paint films. After applying to surface immediately buff it dry with a soft clean cloth. Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency

The product will not perform correctly if applied over non-absorbent surfaces.

Substrate Temperature: +5°C <-> +30°C.

Ambient Temperature: +5°C <-> +30°C.

## **COVERAGE RATE**

The figures below are approximate and should be used only as a general guideline:

**4-8 m<sup>2</sup> / 500 ml.**

## **EQUIPMENT CLEANING**

Immediately after you have finished, clean all tools and equipment with water.

## **STORAGE & SHELF LIFE**

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

## **RECOMMENDATIONS**

Do not use below 4°C. Avoid use in rainy conditions.

## **HEALTH & SAFETY**

**See Material Safety Data Sheet before use.**

Important: The content of this documentation is based on our experience of the product. Lubelska Ltd. guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with GoProtect's products or bad weather conditions. For further information, refer to the safety data sheet.

LUBELSKA PRODUCT CODE: R-47